

Embedded Pneumatic Networks for Soft Robotic Structures: Channel Integrity, Actuation, Fatigue and Control

From printable internal air paths to repeatable soft-robot motion governed by leakage, wall mechanics, chamber geometry and cyclic durability

Juan Seguro

3Dresyns by Resyner Technologies S.L.

© 2026 Juan Seguro. All Rights Reserved.

Correspondence: info@3Dresyns.com · www.3Dresyns.com

ER-369 · Engineering Review · Version 0.2 · 1 October 2026

Abstract

Embedded pneumatic networks convert pressure into motion through asymmetric chamber deformation, so channel geometry, wall mechanics and pneumatic dynamics must be qualified together. Small amounts of uncured or overcured material can strongly change pressure delivery, while viscoelasticity produces creep and hysteresis in the pressure-motion map and leakage can appear first as control drift. The measurement architecture combines inlet pressure and flow, full-field motion or curvature, blocked force, leak rate under hold pressure and cycle-resolved residual deformation. Static pressure-motion-force maps establish the baseline, after which step-response and fatigue tests separate pneumatic, mechanical and leakage contributions. This evidence defines a safe pressure window and the feedback variable needed to maintain actuator output as the structure ages.

Keywords: soft pneumatic actuator; embedded channel; DLP; fatigue; control; pneumatic integrity

1. Qualification problem: embedded pneumatic networks

A defensible qualification record for embedded pneumatic networks links observed behaviour to an explicit operating decision. Here the record covers safe pressure window, whether actuator output should be controlled by pressure, flow or position feedback, and inspection/requalification interval based on drift, with normalised pressure, resistance-compliance time constant, and strain-energy density used to mark changes of regime. [1,2]

1.1 Scope boundary.

ER-369 owns pneumatic-actuator response, including channel integrity, pressure-deformation coupling, fatigue and control. ER-368 owns passive architected flow networks and ER-370 foldable structures; those siblings define adjacent hydraulic and kinematic boundaries.

2. Governing balances for embedded pneumatic networks

Pneumatic actuation is described through scaled pressure, network time response, and local strain-energy demand.

actuation arises from pressure acting on an asymmetric compliant chamber, producing coupled membrane/bending/stretch deformation

flow resistance and chamber compliance set pressure rise time and dynamic bandwidth

large-strain hyperelasticity invalidates small-strain linear models over useful motion ranges

The three variables separate pressure capacity, dynamic response, and local fatigue demand within the embedded network.

3. Regime boundaries for embedded pneumatic networks

The pneumatic map allocates evidence to pressure safety, control strategy, or requalification interval according to the measured regime.

Table 1. Regime indicators for pneumatic-actuator response.

Indicator	Engineering meaning	Use
normalised pressure	actuation pressure scaled by elastic modulus	Check normalised pressure whenever 'safe pressure window' is applied to a different geometry, history or environment; it tracks the relevant change in actuation pressure scaled by elastic modulus.
resistance-compliance time constant	dynamic timescale set by channel resistance and compliance	Check resistance-compliance time constant whenever 'whether actuator output should be controlled by pressure, flow or position feedback' is applied to a different geometry, history or environment; it tracks the relevant change in dynamic timescale set by channel resistance and compliance.
strain-energy density	local elastic energy concentration at hinge or chamber hotspots	Check strain-energy density whenever 'inspection/requalification interval based on drift' is applied to a different geometry, history or environment; it tracks the relevant change in local elastic energy concentration at hinge or chamber hotspots.

Pneumatic performance is transferred only within the pressure, dynamic, and strain-energy combinations demonstrated experimentally.

4. Couplings that move the embedded pneumatic networks

Small uncured or overcured channel deviations change pressure delivery strongly.

Material viscoelasticity causes creep and hysteresis in motion-pressure maps.

Leakage and permeation can appear as control drift before catastrophic rupture.

5. Failure signatures and false diagnoses

Mechanism diagnosis requires the three failure branches—blocked channels, bond/wall rupture, fatigue cracking at chamber corners—to remain distinguishable. pressure and flow at actuator inlet, full-field motion/curvature and blocked force and leak rate under hold pressure are therefore read as complementary evidence rather than interchangeable proxies. Failure attribution also separates channel integrity from actuator mechanics, because leak-free pressure retention does not by itself establish stable motion, dynamic bandwidth or fatigue resistance.

Table 2. Failure-mode discrimination for pneumatic-actuator response.

Failure mode	Observable signature	Discriminating evidence
blocked channels	pressure and flow at actuator inlet	static pressure-motion-force maps
bond/wall rupture	full-field motion/curvature and blocked force	step response across pressure levels
fatigue cracking at chamber corners	leak rate under hold pressure	pressure hold/leak tests before and after cycling
loss of calibration due to permanent set or viscoelastic drift	cycle-resolved hysteresis and residual deformation	fatigue with periodic recalibration of the actuator map

Table 2 distinguishes mechanisms by controlled contrast. The accepted diagnosis is the one that predicts the response ordering across all rows.

6. Measuring embedded pneumatic networks with traceable uncertainty

Qualification measurement is complete only when all three Table 2 observable channels are available with traceable calibration and state metadata. Three independent checks structure the embedded pneumatic networks assessment; during metrology of embedded pneumatic networks, hyperelastic deformation is resolved against fatigue demand. Independent resolution of chamber compliance and pressure rise time establishes the primary state, separate monitoring of fatigue demand tests whether that state survives transfer, and an uncertainty-controlled perturbation of hyperelastic deformation is the perturbation used when the two disagree; the uncertainty record for embedded pneumatic networks keeps fatigue demand separate from chamber compliance.

7. Experiments that discriminate competing mechanisms

The four Table 2 interventions define the discrimination space; attribution is accepted only when one mechanism explains their combined response without contradiction. For the embedded pneumatic networks problem, a replicate test of fatigue demand defines the independent cross-check rather than a tuning variable; during the causal challenge for embedded pneumatic networks, fatigue demand is tested against chamber compliance. The main inference uses a causal contrast between chamber compliance and hyperelastic deformation, whereas a boundary challenge involving pressure rise time is reserved for the boundary test that can overturn the proposed interpretation; the experiment for embedded pneumatic networks separates chamber compliance from pressure rise time.

8. Model identification and validation for embedded pneumatic networks

The first and third branches determine whether it predicts the mechanism rather than merely fitting the training state. [1,2] [3] [4,5] The model output is converted into three separate decision intervals in Table 3, with no pooled nominal-setting correction. Rather than reduce embedded pneumatic networks to one surrogate, the analysis combines an uncertainty-bounded check on fatigue demand with parameter estimation for chamber compliance and pressure rise time; within model identification for embedded pneumatic networks, chamber compliance is not fitted through pressure rise time. A separate prediction against hyperelastic deformation is used to challenge that interpretation, making disagreement between the two routes visible instead of averaging it away; prediction for embedded pneumatic networks keeps pressure rise time independent of hyperelastic deformation.

9. Qualification envelope and technology decisions

Table 3. Technology-decision matrix for pneumatic-actuator response.

Decision	Minimum evidence	Acceptance logic
safe pressure window	Support safe pressure window with state-resolved pressure and flow at actuator inlet measurements that bracket the candidate condition and quantify both repeatability and uncertainty.	Accept only where the response of pressure and flow at actuator inlet to 'static pressure-motion-force maps' remains reproducible across the transfer states and blocked channels is absent.
whether actuator output should be controlled by pressure, flow or position feedback	The evidence set for whether actuator output should be controlled by pressure, flow or position feedback should contain calibrated full-field motion/curvature and blocked force measurements from baseline through the proposed limit, with independent replication near that limit.	Accept only if 'step response across pressure levels' leaves full-field motion/curvature and blocked force inside the qualified response band and no bond/wall rupture signature appears.
inspection/requalification interval based on drift	Evidence must include calibrated leak rate under hold pressure in reference and candidate states, with replicate measurements that resolve the margin for inspection/requalification interval based on drift.	Retain the decision only where 'pressure hold/leak tests before and after cycling' produces the expected bounded change in leak rate under hold pressure; evidence of fatigue cracking at chamber corners rejects the transfer.

An acceptable record for embedded pneumatic networks must show an explicit transfer limit on fatigue demand without inferring it from tested ranges in chamber compliance and pressure rise time; inside the embedded pneumatic networks envelope, pressure rise time and hyperelastic deformation define different transfer limits. In parallel, a separate boundary for hyperelastic deformation probes the boundary

condition most likely to change the interpretation, and the resulting uncertainty is carried forward explicitly; qualification of embedded pneumatic networks bounds hyperelastic deformation separately from fatigue demand.

10. Design consequences for embedded pneumatic networks

The qualified design space is the overlap of the three Table 3 rows, not the best value of any one metric. Implementation is separated into a design change governed by chamber compliance and an implementation check on hyperelastic deformation; while safe pressure window is controlled independently, a change in a requalification trigger tied to fatigue demand prevents the new setting from being called equivalent; during design implementation for embedded pneumatic networks, hyperelastic deformation is constrained by fatigue demand. The consequence is a bounded design decision with a defined route back to validation; the embedded pneumatic networks design record separates fatigue demand from chamber compliance.

11. Evidence gaps for embedded pneumatic networks

The first and third branches should accompany that extension so that selectivity is preserved. Uncertainty in pressure rise time versus hyperelastic deformation is the first stress test for embedded pneumatic networks; only after that result is bounded is scale transfer of chamber compliance interpreted; for unresolved embedded pneumatic networks transfer, fatigue demand is studied separately from chamber compliance. The record keeps independent replication of fatigue demand outside that inference and reports it as an independent line of evidence; the evidence gap in embedded pneumatic networks distinguishes chamber compliance from pressure rise time.

12. Qualification outcome for embedded pneumatic networks

The qualification result consists of three explicit Table 3 limits, each tied to its own evidence route. Qualification of embedded pneumatic networks treats agreement between measurement and prediction for chamber compliance as one axis and a renewed-evidence trigger when fatigue demand changes as another; at final qualification of embedded pneumatic networks, chamber compliance is reconciled with pressure rise time. Between them, causal evidence that separates pressure rise time from hyperelastic deformation supplies the deliberate challenge that determines whether the apparent transfer is mechanistic or merely coincidental; the closing embedded pneumatic networks claim keeps pressure rise time distinct from hyperelastic deformation.

References

1. Ge L, Dong L, Wang D, Ge Q, Gu G. A digital light processing 3D printer for fast and high-precision fabrication of soft pneumatic actuators. *Sensors and Actuators A: Physical*. 2018;273:285-292. doi:10.1016/j.sna.2018.02.041.
2. Zhang Q, Weng S, Zhao Z, Qi HJ, Fang D. Soft pneumatic actuators by digital light processing combined with injection-assisted post-curing. *Applied Mathematics and Mechanics*. 2021;42(2):159-172. doi:10.1007/s10483-021-2705-7.
3. Xavier MS, Tawk CD, Yong YK, Fleming AJ. 3D-printed omnidirectional soft pneumatic actuators: Design, modeling and characterization. *Sensors and Actuators A: Physical*. 2021;332:113199. doi:10.1016/j.sna.2021.113199.
4. Song Y, Park B, Jeon S, Kweon H, Lee S, Na J. Machine learning guided formulation design of digital light processing printable elastomers beyond viscosity stretchability tradeoff. *Nature Communications*. 2026;17:7167. doi:10.1038/s41467-026-73735-4.
5. Lu C, Hsieh M, Huang Z, Zhang C, Lin Y, Shen Q, Chen F, Zhang L. Architectural Design and Additive Manufacturing of Mechanical Metamaterials: A Review. *Engineering*. 2022;17:44-63. doi:10.1016/j.eng.2021.12.023.

Competing interests

The author is Founder, CEO and CTO of 3Dresyns by Resyner Technologies S.L. No comparative product recommendation is made.

Data availability

No new experimental dataset was generated for this review.